

Utility Patent Application

35 UCS 112, Specification Section w/Abstract

Conversion of Provisional Patent 60/410,694

Inventor: S.P. Broussard, III

Greenwell Springs, Louisiana 70739

E-Z Gooseneck/Fifth Wheel Conversion System

CROSS-REFERENCE TO RELATED APPLICATION

This application is based upon, and claims the benefit of, my provisional Application No. 60/410,694, filed September 8, 2002.

FIELD OF INVENTION

This invention relates to a trailer and camper, fifth-wheel hitch, hitch conversion and towing vehicle bed space saving system.

BACKGROUND OF THE INVENTION

This specification of my application is a description of an invention which is an easily installed and removed device for the connection of a towed vehicle (recreational vehicle [RV], camper, horse trailer, large flatbed, etc) to a tow vehicle with a bed for locating a conventional steel ball (pick up truck). This gooseneck adapter will convert a "king-pin fifth-wheel type couple" common on RVs, campers, horse trailers to a towing vehicle's truck mounted conventional steel towing ball. Heretofore, fifth-wheel type trailers required a mating part that is semi permanently mounted in the bed of the pick-up/ towing truck, thus causing a space-restricted use of the pick-up truck for other general use, requiring a cumbersome effort and tools to mount and remove. Furthermore, prior conversion kits the such as in the case of US Patent 6,416,073, are more structurally complex and hence more costly to manufacture versus the E-Z gooseneck/fifth-wheel conversion system.

SUMMARY OF THE INVENTION

In accordance with the present invention there is provided an easy fifth-wheel to gooseneck trailer hitch conversion which can be connected or removed from the king pin of a fifth wheel trailer to be towed by a vehicle having a ball type hitch mounted in the bed of the towing vehicle; a ball which may be designed per this invention to be removable, leaving the pick-up truck's bed unrestricted.

Patent Application: Specification

Inventor: S. P. Broussard III

Conversion of Provisional Application: 60/410,694

In the preferred embodiment of this invention, the hitch conversion system comprises:

- (a) a one half inch thick carbon steel thrust plate and a tapered split ring which permits the insertion of the king pin of a fifth-wheel type trailer;
- (b) a nominal 4 inch schedule 80 carbon steel cylinder to which the carbon steel thrust plate is welded and the body of the cylinder is typically 11 inches long (usually in the range 9-12 inches);
- (c) no less than two or more than eight tapered set screws in the cylinder body in order to securely lock to the trailer's king pin and king pin plate;
- (d) a lower unit, standard 59 mm SAE Class 3 ball coupling, which may be modified for special application as required;
- (e) an ISO standard 3853/1103 59 mm ball installation that is removable and a hole plug to enable a totally unobstructed bed serves as an optional feature of the E-Z gooseneck/fifth-wheel system.

The E-Z fifth-wheel conversion system is *not* welded to the camper trailer nor is it required or necessary to drill holes in the existing fifth-wheel hitch of the trailer.

BRIEF DESCRIPTION OF THE DRAWINGS

This invention is explained in more detail utilizing the accompanying figures/drawings, which are recognized and referenced in the detailed description of this specification. The figures included as a part of this specification are:

- (a) FIG. 1 which is a cut-a-way view of the fifth-wheel trailer king pin, the tapered split ring, the tapered set screws, the cylinder assembly body, and the location of the ball connection;
- (b) FIG. 2 is a more detailed, exploded view of FIG 1;
- (c) FIG. 3 demonstrates one perspective of a fifth wheel trailer in relationship to the bed of a towing vehicle;
- (d) FIG. 4 demonstrates the center placement of a removable towing ball and a replacement plug when the ball has been removed.
- (e) FIG. 5 is a cut-a-way rear views of the installation, removal and plugging of the conventional trailer ball to which the E-Z gooseneck /fifth-wheel conversion kit is connected to at the bottom end of the kit.

Patent Application: Specification

Inventor: S.P. Broussard, III

Conversion of Provisional Application: 60/410,694

DETAILED DESCRIPTION OF THE INVENTION

The E-Z gooseneck/fifth-wheel trailer conversion system shown in FIG 3 and illustrated in the additional drawings serves to attach to a vertically-oriented fifth-wheel king pin **10** carried by a horizontal plate **7**.

The king pin **10** sits into the conversion assembly column **3**. The upper end of **3** consists of a thrust plate **4** which may be 7/16 inch to 3/4 inch thick, and is 7 to 9 inches in diameter and made of heavy duty metal (carbon steel through any specialty stainless steel, titanium or any metal alloy or combination having a Brinell hardness number (BHN) of at least 130 and a tensile strength of at least 50,000 psi). This thrust plate **4** serves to distribute the horizontal and vertical load to a larger surface area of the existing king pin plate **7**. A tapered ring **6** which has been machined having an I.D. the same as the minor O.D. of the king pin groove **11** and having an O.D. the same as the larger dimension of the king pin **10**. This tapered ring **6** is split into two equal parts and inserted into the existing king pin groove **11**. A bushing, bushing not shown, fills in the space between the O.D. of the king pin and the I.D. of the extension section **3**. Set screw threads **20** are drilled into the extension column **3**. A minimum of three (3) and a maximum of eight (8) such set screws **8** may be used, though as many screws as desired would be suitable. These set screws **8** have machine-tapered ends **21** being the same angle as the tapered split ring **6**. These tapered set screws **8** and the matching tapered split rings **6** are key to the conversion units utility. Using a simple Allen wrench, the set screws **8** are tightened by hand against the tapered part of the split ring **6** and causes the device to become firmly and securely locked to the existing king pin **10** and the existing king pin plate **7**. The slightly initial tightening of two of the set screws **9** will hold the conversion column (typically 30 - 40 pounds in weight) in place while tapered set screws **8** are adjusted and tightened in place.

The E-Z conversion unit column **3** consists of a length of metal pipe made of material with a BHN exceeding 130 and a tensile strength of at least 50,000 psi with an outside diameter in the range of 3.5 to 5.6 inches with an inside diameter in the range of 3.0 to 5.1 inches and a wall thickness in the range of 0.2 to 0.3 inches. The length of the extension column unit **3** of the conversion unit may be of a length from 9 to 12 inches depending on the trailer and truck used; the most common length based on analysis of several unit combinations is 11 inches in length.

The lower section **2** of the conversion column **3** is a conventional SAE qualified class coupling for an ISO standard 50 - 59 mm ball that is manufactured by various suppliers. This coupling is typically and ideally spring-loaded for easy release from the ball **13** remotely by way of a lanyard.